

# Robust but compact: 3m drop resistance – IP67 – 280g



Now available with  
All-Range-Imager and  
RFID/NFC functionality

- Windows® Embedded CE 6.0 R3
- All-Range-Imager
- 3.0m drop resistance and IP67
- RFID/NFC available
- 280g light and highly ergonomic
- 2.7 inch QVGA-touch display

# The handy All-Range terminal: Precise scanning up close and at long range



With its optional All-Range function, the DT-X8 offers virtually unlimited possibilities when it comes to mobile data logging – and what’s more, it is a highly ergonomic, compact and robust device. The high-performance CMOS auto-focus imager reads two-dimensional codes with high data volumes, such as DataMatrix, Aztec, PDF417 and many other stacked codes.

The imager reads all common barcodes (depending on the line thickness) at close proximity and at long range, with its highly visible laser pointer target beam and the auto-focus imager ensuring secure and rapid reading over short and long distances.

**The highly visible laser pointer enables precision scanning at long distances**



## RFID and NFC functionality

The optional RFID module is integrated in the front of the DT-X8 terminal to ensure ease of use. Including the read/write antenna, the HF module weighs a mere 5g. With a range of approximately 10cm, the DT-X8 reads and writes RFID tags in accordance with the ISO15693 standard. Take advantage of our extensive experience in RFID technology, with many

thousands of devices on the market. An RFID tag offers considerably greater memory capacity than a 2D code. RFID tags are also known for their increased durability – problems associated with unreadable, damaged or dirty barcodes belong to a thing of the past. As there is no need for any optical contact to enable communication between the RFID tag and the hand-held

device, it is also quicker and easier to transfer data.

When it comes to Near Field Communication(NFC), the device supports the ISO14443 and ISO15693 standards. NFC technology can be used, for example, to complete a range of tasks in the fields of employee authentication and access control.

## Smaller, more versatile and even more robust

Whenever you need to scan a lot and scan quickly in a harsh environment, the new CASIO DT-X8 is at home. The DT-X8 impresses supporters of small, lightweight and ergonomic hand-held devices, as well as those who primarily emphasize reliability and robustness. The DT-X8 was specially developed for the tough working conditions in warehouses. The goal for the Japanese

developers was producing a device with excellent ergonomics under tough conditions, as well as optimum functionality.

On the one hand, the DT-X8 is considerably more compact than traditional warehouse hand-held terminals, and on the other hand, it is clearly more robust than other devices with similar dimensions.

## Outstanding robustness



The DT-X8 is shock protected against drops from height of up to 3 metres onto concrete. This completely covers all impacts and fall heights that typically occur in a warehouse. The terminal withstands dust and temporary immersion in water in accordance with protection class IP67 and it works at temperatures down to -20°C. This guarantees that the device can be used outdoors the whole year, as well as in cold stores, wet areas and in particularly dusty or dirty environments.

## Powerful technology


The CASIO DT-X8 comes with a PXA320 processor with a 624-MHz frequency, 128 MB RAM, 256 MB FROM memory and uses Windows® Embedded CE 6.0 R3. With the powerful 2.860-mAh lithium-ion battery, this lightweight device, which only weighs 280g, can work up to 25 hours.



## Comfortably simple handling, perfect scanning



From the very first glance, the rolling S-shaped design of the DT-X8 suggests excellent ergonomics. This is another device developed by CASIO under the principles of Human-centred Design. Enlarged, easily accessible keys for the basic functions make the device easy to use with one hand, particularly when scanning – with or without gloves. The optional CMOS-Imager reads a wide range of 1D and 2D codes, including the latest GS1-DataBar and QR-codes. Three ergonomic scan buttons – one in the middle and one each on the left and right side of the housing – enable both right-handed and left-handed users to hold the device in



different working positions and work with the least possible hand and finger movement. The scan direction points diagonally downwards for intuitive, fast scanning, allowing the user to read the display during the scanning process. If adjacent barcodes are scanned, the laser focus function shows the user which barcode is being scanned by briefly illuminating it red. Scan confirmation using a vibration function provides additional security.



## Energy-saving, high-contrast touch screen

The high-contrast colour display of the DT-X8 with LED back-light enables user-friendly data input via the touch screen. The user can operate softkeys or capture signatures on the display itself. The particularly translucent BlanView® display provides optimum readability in darkness and in strong sunlight whilst at the same time extremely low power consumption.



## Unlimited wireless communication

For data exchange, the DT-X8 is equipped with Bluetooth® 2.0 with EDR, WLAN (IEEE802.11b/g) and WPA2 encryption as standard. Thanks to the built-in microphone and loudspeaker, users can handle VOIP calls and record memos.

## Complete bundle as standard

For the first time, CASIO is offering the DT-X8 as a complete set — with all the accessories required for immediate use: 2.860-mAh battery with mains AC adapter, USB cable, communication (USB) and charging adapter, wrist strap and stylus.



## General Guide /Options

**Left Side**

- Receiver
- Screen
- Trigger Key
- Center Trigger Key
- Keyboard
- Color Coded Function Keys

**Front**

- Status LED
- Power on/off
- Cursor Key
- Screen Protect Sheet HA-K90P55

**Back**

- Laser-Scanner/CMOS-Imager
- Expansion Port
- Trigger Key
- Battery Case
- Lithium-ion battery HA-K23XLBAT

**Right Side**

- microSD Card Slot

**Accessories:**

- USB and Charging Unit HA-K65US
- USB Cable DT-380USB-A
- USB Cradle HA-K60IO
- USB/Ethernet Cradle HA-K62IO
- Dual Battery Charger HA-F32DCHG
- Double Charging Cradle HA-K36DCHG
- AC Adapter AD-S15050B-N5
- AC Adapter AD-S42120C-N5
- AC Adapter for Double Cradle AD-S90190C-N5
- Hand Belt HA-K95HB

## DT-X8 All-Range: Optimising processes, adding value

The DT-X8 is an extremely compact, light and highly robust terminal that sets a new standard in warehouse environments and is second to none in terms of user benefits, reliability and investment security. The top-of-the-range DT-X8 All-Range model also features RFID and NFC functionality. It is ideal for reading large data volumes – whether at close proximity

or at long distances – from a wide range of data sources and in the shortest possible time with minimal error rates. This means employees do not need to move over long distances, increasing pick rates in the warehouse and the low error rates also help to improve data quality in the company.



## Maximum benefit, minimal TCO – in typical CASIO style



The DT-X8 is highly versatile; it can be used indoors or outdoors, in wind and bad weather, under difficult lighting conditions and in extremely dusty and dirty environments. The high product quality, decades of experience

in the toughest mobile application segments – such as parcel delivery and warehouse logistics – and high level of acceptance amongst employees ensure a predictable, low TCO (Total Cost of Ownership) and a smooth project launch phase.



Specifications						
Model	DT-X8-10E	DT-X8-11E	DT-X8-20E	DT-X8-21E	DT-X8-40E	DT-X8-41E
Laser-Scanner	X	X				
CMOS-Imager			X	X		
All-Range-Imager					X	X
RFID/NFC Function		X		X		X
Model	DT-X8-10E	DT-X8-11E	DT-X8-20E	DT-X8-21E	DT-X8-40E	DT-X8-41E
CPU	Marvell® PXA320 624MHz					
OS	Microsoft® Windows® Embedded CE 6.0 R3 English Version					
Durability	Drop Durability	3.0m				
	Dust/Splash-Proof	IP67 (compliant with IEC60529 standard)				
	Operating Temperature	-20°C to 50°C				
Memory	RAM	128MB				
	ROM	256MB (User area: Approx.160MB)				
Display	LCD	BlanView® TFT Color LCD with Touch Panel 6.9cm (2.7 inches) QVGA (240x320 pixel)				
	Indicator	Indicator 1: Battery charging status Indicator 2: Scanning and wireless communication status				
Input	Keyboard	32 keys, numeric (Alphabet) keys, CLR key, execute key, cursor keys, power key, Fn key, F1 to F8 keys, L/R keys				
	Trigger	3 (at center, left, and right)				
	Touch Panel	Yes (Resistive type)				
NFC	Standard		NFC Interface Protocol-2 (ISO21481)		NFC Interface Protocol-2 (ISO21481)	NFC Interface Protocol-2 (ISO21481)
	Carrier Frequency		13,56MHz		13,56MHz	13,56MHz
	RFID		ISO15693 I-CODE SLI®, Tag-it® and my-d®		ISO15693 I-CODE SLI®, Tag-it® and my-d®	ISO15693 I-CODE SLI®, Tag-it® and my-d®
	Contactless Smart Card Reader/Writer		ISO14443 Typ A/B Mifare® and FeliCa® Technology		ISO14443 Typ A/B Mifare® and FeliCa® Technology	ISO14443 Typ A/B Mifare® and FeliCa® Technology
Scanner	Type	Semi-conductor Laser		C-MOS Imager		All-Range-Imager*
	Resolution	0.127mm		1D: 0.15mm, Stacked: 0.169mm, Matrix: 0.25mm		1D: 0.127mm; Stacked: 0.127mm; Matrix: 0.169mm
	1D	GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, MSI, Interleaved 2of5 (ITF), Industrial 2 of 5		GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, Code11, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, MSI, Interleaved 2 of 5 (ITF), GS1 DataBar Truncated		GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, Code11, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, MSI, Interleaved 2 of 5 (ITF), ISBT, Code 32, GS1 DataBar Truncated
	Stacked	GS1 DataBar Omnidirectionalstacked, GS1 DataBar Expanded Stacked		GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Code49, PDF417, Micro PDF, Composite, Codablock F, TLC39, GS1 DataBar Truncated		GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, PDF417, Micro PDF, Composite, Codablock F
	Matrix			Aztec, DataMatrix, Maxicode, QR Code, Micro QR, HanXin Code		Aztec, DataMatrix, Maxicode, QR Code, MicroQR
Wireless LAN	Standard	IEEE 802.11b (Maximum: 11Mbps), IEEE 802.11g (Maximum: 54Mbps)				
	Security	WPA2/AES				
Interfaces	Bluetooth®	Bluetooth® Version 2.0+EDR compatible				
	Card Slot	microSD Memory Card (SDHC) x 1				
	USB	Version 1.1 (Host/Client)				
	Audio	Microphone: Built-in (monaural), Speaker: Built-in (monaural)				
Power	Main Power	Lithium-Ionen-Akku: 3,7V/2.860mAh, Large-capacity lithium-ion battery pack				
	Operating period	Approx. 25 hours		Approx. 20 hours		
	Memory Backup	Lithium-ion battery (rechargeable) on board				
Vibrator	standard					
External Dimensions (WxDxH)	Ca. 65.8 (57.4) x 187.5 x 44.2 (35.0) mm *The figure indicates the grip part.					
Weight Including lithium-ion-battery pack	Approx. 280g	Approx. 285g	Approx. 280g	Approx. 285g	Approx. 290g	Approx. 295g

\* The reading range depends on the resolution and size of the barcode/ident code

Powered by Windows® and Windows® Embedded are registered trademarks of the Microsoft Corporation, USA. The Bluetooth trademark is owned by Bluetooth SIG, USA and licensed to Casio Computer Co. Ltd.. Other product- or company names are either trademarks or registered trademarks of the respective owners. This publication carries product description without obligation and is not to be seen as a firm offer. Specifications and design are subject to change without notice.

