



## PLANETLUX LABELS

### Technical data sheet

#### FACE MATERIAL:

<b>Description</b>	Woodfree, uncoated, smooth finished paper
<b>Use</b>	Multifunctional information labelling, corporate stationery, and VIP papers. Printable with ink-jet, laser and copier.

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	92	93

#### ADHESIVE:

<b>Description</b>	A general permanent adhesive for laser applications.
<b>Performances</b>	Very good adhesion for general use with paper labels. Good heat resistance.
<b>Shelf life</b>	2 years stored at 22°C and 50% RH

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N/mm	°C	°C	°C
	9	+5	-10	+100

#### BACKING PAPER:

<b>Description</b>	White woodfree kraft backing paper
<b>Application</b>	For laminates where thin backing is needed for information labelling.

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	51	54

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.