

PL310020



AP 360e Label Applicator is the perfect semi-automatic labeling solution for cylindrical containers as well as many tapered containers, including bottles, cans, jars and tubes. The built-in spring-loaded pressure arm makes sure labels are applied firmly and without wrinkles. It's able to apply labels at speeds of up to 1200 per hour. Thanks to its compact size fits on most desks and countertops

AP360 Label Applicators Specifications

Container Width:	1" to 9.4" (25.4mm to 238mm)
Container Diameter:	0.6" to 6.7" (15mm to 170mm)
Container Shape:	Cylindrical and many tapered
Supply roll diameter:	Up to 8" (203mm)
Media liner width:	1" to 8.375" (25.4mm to 213mm)
Supply roll core:	2" to 3" I.D. (51.8mm to 76.2mm)
Electrical rating:	12VDC, 5.0A
Power requirements:	100-240VAC, 50/60 Hz, 60 watts
Agency certifications:	UL, UL-C, CE, FCC Class A
Weight:	16 lbs. (7.26 kg)
Dimensions:	13.4"W x 8.9"H x 12.9"D (340mmW x 226mmH x 328mmD)
Gap between Labels:	Recommended: 1/8" - 1/4" (3.175 mm - 6.3500 mm)
Label Type:	Die cut with waste removed. Clear labels can be used.
Liner Thickness:	2 mil - 10mil (smoothness will affect feeding - a liner that is too slippery or too thin will slip through the drive rollers)
Label + Adhesive Thickness:	5 mil - 15 mil*
Wind Direction	Wound out - See Copy-Position Chart (Position 3 or 4 for most containers)