

enjoyid



jolly

STABLE
OMNIDIRECTIONAL
RELIABLE

APPLICATION FIELDS

- Point of Sales - Cash Registers
- Catering
- Office Automation
- Pharmacy
- Kiosks and vending machines
- Turnstiles



Barcode
readers & scanners

TECHNICAL FEATURES



Category

GENERAL

Interface KB wedge, RS-232, USB

Barcode supported EAN-13, EAN-8, UPC-A, UPC-E, Code 128, Code 93, CodaBar Code 39, Code 39 extended, Code 11, Code 32, EAN-128 Chinese Postage Code, IATA, MSI/PLESSY, STD 2 of 5, Matrix 2 of 5, Interleave 2 of 5, Italian Pharmacy Code, Industrial 2 of 5, RSS-14, RSS-Limited, RSS-Expanded

Laser Class 1 EN 60582-1 : 1994 + A11:1996 + A2:2001

OPTICAL

Light source Laser diode 650nm

Resolution 5 mil

Depth of Filed 25 mm ~ 279 mm for EAN/UPC 100% (13 mil)

Scan rate 1.650 scans/sec.

ELECTRICAL

Voltage + 5V±10%

Reading indicator Beeper and Two-color LED (Blue and White) / Blue = Laser on , ready to scan - White = good read

ENVIRONMENT

Operating temperature -20°C ~ 40°C

Storage temperature -40°C ~ 60°C

Operating humidity 5%RH ~ 95%RH

Storage humidity 5%RH ~ 95%RH

Safety Approval FCC Class-B, CE Class-B, EMC, U/C CSA

PHYSICAL

Weight 410 g excluding Cable and Connector

Dimensions 110 mm (L) X 115 mm (W) X 240 mm(H)

Cable length 2 mt

Connector RJ45 phone jack connector 10 pins

Warranty 1 year

Product specification subject to change without prior notice.



enjoyid