

ESSENTIAL ERGONOMIC RELIABLE

APPLICATION FIELDS

- Point of Sales Cash Registers
- Catering
- Office Automation
- Hospital and Health service
- Pharmacy



TECHNICAL FEATURES

Category



GENERAL	
Interface	KB wedge, RS-232, USB
Barcode supported	EAN-13, EAN-8, UPC-A, UPC-E, Code 128, Code 93, CodaBar Code 39, Code 39 extended, Code 11, Code 32, EAN-128 Chinese Postage Code, IATA, MSI/PLESSY, STD 2 of 5, Matrix 2 of 5, Interleave 2 of 5, Italian Pharmacy Code, Industrial 2 of 5, RSS-14, RSS-Limited, RSS-Expanded
OPTICAL	
Optical sensor	2048 pixel
Light source	Visible LED (660nm)
Resolution	4 mil
Depth of Filed	0 mm~25 mm
Scan rate	100 scans/sec.
ELECTRICAL	
Voltage	+ 5V <u>±</u> 10%
ENVIRONMENT	
Operating temperature	0 °C to 50 °C
Storage temperature	-26 °C to 60 °C
Operating humidity	> 80%
Storage humidity	> 90%
PHYSICAL	
Weight	190 g (w/cable)
Dimensions	166mm (L) x 78,8mm (W) x 55,5mm (H)
Housing Material	ABS plastic
Garanzia	1 year

Product specification subject to change without prior notice.

