



PAPER HEALTH DIVISION

Technical data sheet

FACE MATERIAL:

- Description** A white, surface-sized, supercalendered woodfree printing paper. The facestock is made with FSC certified pulp
- Use** The material provides good print resolution of picket fence barcodes and numeric data with thermal transfer print speed up to 150mm/sec..

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	68	66

ADHESIVE:

- Description** A permanent, rubber based adhesive.
- Performances** The adhesive features excellent tack and adhesion in a wide variety of substrates, including apolar, slightly rough and curved substrates. The adhesive can be used in direct contact with dry and moist, non fatty foodstuffs.
- Shelf life** 2 years under storage conditions : 20-25°C ; 40-50% RH)

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N/mm	°C	°C	°C
	22N/25mm	5	-40	+70

BACKING PAPER:

- Description** A brown supercalendered glassine paper

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	57	51

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.